

Mitutoyo

Mitutoyo Quality

Compact Roundness Measurement ROUNDTEST RA-120/120P

Form Measurement



Catalog No.E15008(4)

Roundtest RA-120

This compact roundness measuring machine is provided with numerous user-friendly features aimed at prioritizing usability, such as a wider range for the detector, an easy-to-understand operation panel with large LCD, a D.A.T. function that powerfully supports centering and leveling adjustments, and so on.

- Best-in-class rotational accuracy in compact type roundness measuring instruments
- Fine adjustment on both X- and Z-axes
- Multiple analyses through simple operation
- D.A.T. function^{*1}
- Scaled Z-axis^{*1}
- Continuous ID and OD measurement^{*1}
- High-precision air bearing
- Wide-range detector^{*2}
- Registration and calling of measurement results/ conditions
- Built-in printer
- Supports 16 languages

^{*1} Refer to P.6

^{*2} Refer to P.7




Simple, interactive display screen

The large LCD screen with backlight shows easy-to-understand measurement results and graphs. Forms can be checked and notch processing can be set while observing the displayed graphs.


Measurement screen

- Set the position of the detector and measurement conditions here
- During measurement, graphs are displayed in real time



Measurement results

- Filter, display magnification, etc., can be altered
- Besides circles, development views can also be displayed



Operating panel that is read at a glance

Supports 16 languages

Japanese, English, German, French, Italian, Spanish, Portuguese, Korean, Traditional Chinese, Simplified Chinese, Czech, Polish, Hungarian, Turkish, Swedish, Dutch

Analysis type

Selection buttons provide access to a wide variety of analysis types



Simple setup

Apply the current measurement setup in one go
Simple operation helps prevent operational errors

Jog dial

Make detailed changes to setup and other operations

Switching screen modes

Switch the display at the touch of a button, providing access to the [Calibration], [Centering and Leveling], [Measurement], and [Result] screens.

Zero-setting button


No fine adjustment necessary for setting the measurement position

Simplified communication program for ROUNDTEST RA-120

The Roundtest RA-120 has a USB interface, enabling data to be transferred to a spreadsheet or other software.

Notch processing


Unwanted data, such as that produced by notches or scratches, can be excluded from the analysis if desired. Select between [Automatic setting] and [Arbitrary setting].



High-grade thermal printer

Print measurement conditions, computation results, result graphs, comments, etc., to the thermal printer. Change development graphs and output items as desired.

Sample prints



File save

Save and access [Measurement files] and [Result files] in USB memory. Data can also be totaled using the data output function with commercial tabulation software.

[Measurement file] [Measurement data (Data output)]
[Result file] [Result data (Data output)]

Recording paper set (optional set of 10 rolls)

Roundtest RA-120P

This entry-level desktop tester incorporates the ROUNDPAK multi-analysis evaluation program, which provides it with analytical power close to that of more elaborate models. This is, therefore, a highly functional multi-analysis roundness measuring machine that is suitable for use not only in measurement rooms, but also in research and development sections.

- Best-in-class rotational accuracy in the Compact Type Roundness Measuring Instruments
- Fine adjustment on both X- and Z-axes
- Multiple analyses through simple operation
- D.A.T. function^{*1}
- Scaled Z-axis^{*1}
- Continuous ID and OD measurement^{*1}
- Display function for various graphs
- High-precision air bearing
- Wide-range detector^{*2}
- Supports 18 languages


^{*1} Refer to P.6

^{*2} Refer to P.7




Windows graphical interface

By using a mouse and buttons, identified by corresponding icons, to control the machine, the Roundtest RA-120P's interface provides excellent usability. Functions such as recalculation and graph reading are handled swiftly with easy-to-understand operations.




This entry-level desktop tester incorporates the ROUNDPAK multi-analysis evaluation program, which provides it with analytical power close to that of more elaborate models. This is, therefore, a highly functional multi-analysis roundness measuring machine that is suitable for use not only in measurement rooms, but also in research and development sections.

Measurement screen makes ample use of graphs




Multi-analysis function

Complete with a wide range of functions including partial enlargement, auxiliary line setup, color change, displacement/angular difference of data between two points, and so on. Also equipped with notch processing and graph reading functions, which make the machine useful in research departments. Recalculation can also be performed with the filter and evaluation method changed.



Simplified layout function



Computation results for multiple items can be laid out in multiple forms on a single sheet and printed. This function also supports output to a color printer (optional).



Functions that implement greater efficiency of measurement and range of analysis types

D.A.T. function *except for centering/leveling device (analog micrometer heads)


This instrument uses the D.A.T. (Digital Adjustment Table) function available on more sophisticated models, and this provides powerful support for centering and leveling operations. To perform such operations, the user need only adjust the digital micrometer heads attached to the rotary table by the amounts indicated by the display. This function also supports measurement of notched workpieces.



Continuous ID and OD measuring function

This function comes in very handy when outside diameter and inside diameter surfaces need to be measured repeatedly, for example, with respect to coaxiality, deviation in wall thickness, etc. The inner surface can be measured and evaluated with the detector, maintaining the same measuring position for the outside diameter without changing its orientation, as illustrated on the right.

Inside diameters down to 50 mm can be measured.



Continuous inside and outside diameter function (inside dia. surface)

Continuous inside and outside diameter function (outside dia. surface)


Z-axis scale

This scale is useful when the measuring height position needs to be entered, such as when measuring coaxiality, etc. The machine uses an ABS Digimatic scale unit to provide an effective means for repetitive measurement and position setting.



IN/OUT switchable wide-range detector

The range of this detector has been extended from that of a conventional lever head by as much as four times, and is now wider than ever before. The detector can provide sufficient margin for centering and leveling jobs, or when measuring large differences. Moreover, the measuring direction can be switched between inside and outside diameters with a single touch of a button.



Types of Analysis

Type of Analysis	Measurement mode	Evaluation diagram	RA-120	RA-120P	Type of Analysis	Measurement mode	Evaluation diagram	RA-120	RA-120P
Roundness			✓	✓	Parallelism			✓	✓
Flatness			✓	✓	Radial			✓	✓
Relative to Axis			✓	✓	Thickness variation			✓	✓
Relative to Plane			✓	✓	Axial			✓	✓
Concentricity			✓	✓	Radial			✓	✓
Of section			✓	✓	Circular run-out			✓	✓
Coaxiality			—	✓	Axial			✓	✓
Of axis			—	✓	Power spectrum			—	✓
			—	—	Profile operation			—	✓

Optional Accessories

■ Interchangeable Stylus

12AAL021 Standard stylus	*Standard accessory (stylus tip: Ø1.6 carbide ball)	12AAL022 Stylus for notched workpieces (stylus tip: Ø3 carbide ball)	12AAL023 Stylus for grooves (stylus tip: R0.25 sapphire)	12AAL024 Stylus for corners (stylus tip: R0.25 sapphire)			
	For standard applications		Useful for notched workpieces		For stepped applications		For inside-corner applications
12AAL029 Stylus for extra small holes (stylus tip: Ø0.5 carbide ball)		12AAL026 Stylus for small holes (stylus tip: Ø0.8 carbide ball)		12AAL030 Stylus for small and deep holes (stylus tip: Ø1.6 carbide ball)		12AAL028 Stylus for small and deep holes (stylus tip: Ø1.6 carbide ball, L=40)	
12AAL027 Stylus for small holes (stylus tip: Ø1 carbide ball)		12AAL032 Cranked stylus (stylus tip: Ø0.5 carbide ball)		12AAL033 Cranked stylus (stylus tip: Ø1 carbide ball)		12AAL034 Stylus for flat surface	
12AAL025 Stylus for filtering asperities (machining marks)		12AAL031 Disk stylus		12AAL043 M2 tapped shank for CMM stylus		12AAL044 M2 tapped shank for CMM stylus	

*□ portion shows stylus except for the cranked stylus and stylus for flat surface.

*Customized special interchangeable stylus are available on request. Please contact any Mitutoyo office for more information.

■ Centering chuck (knurled ring operated)

Provides good operability when measuring a small-diameter workpiece. The knurled ring allows the workpiece to be clamped easily.



Order No.	211-032
Holding range	OD with inner jaw: Ø1 - 36 mm ID with inner jaw: Ø25 - 69 mm OD with outer jaw: Ø25 - 79 mm
External size (DxH)	Ø118 x 41 mm
Mass	1.2 kg

■ Three-jaw chuck (key operated)

Useful where it is necessary to apply a higher clamping force to the workpiece than can be applied with the centering chuck.



Order No.	211-014
Holding range	OD with outer jaw: Ø2 - 35 mm ID with inner jaw: Ø25 - 68 mm OD with outer jaw: Ø35 - 79 mm
External size (DxH)	Ø157 x 70.6 mm
Mass	3.8 kg

■ Microchuck

For clamping a small workpiece, 1 mm or less in diameter, that cannot be held in the centering chuck.



Order No.	211-031
Holding range	OD: Ø0.2 - Ø1.5 mm
External size (DxH)	Ø107 x 48.5 mm
Mass	0.6 kg

■ Auxiliary stage for a short workpiece

356038



■ Reference hemisphere

211-016



■ Magnification checking gage

211-045



■ Gage block set for calibration

997090



■ Printer paper 10 roll/set

12AAH181



■ Replacement elements for the air filter

358592 (for filter)


358593 (filter regulator)



Order No.	12AAH320
Vibration damping system	Diaphragm type air spring
External size	615 x 515 x 51 mm
Max. loading mass	150 kg

■ Simplified communication program for ROUNDTEST RA-120

The Roundtest RA-120 has a USB interface, enabling data to be transferred to a spreadsheet or other software. We also provide a program that lets you create inspection record tables using a Microsoft Excel* macro.



Required environment:

- OS: Windows XP-SP3
Windows VISTA
Windows 7 (32bit/64bit)
Windows 10
- Spreadsheet software: Microsoft Excel 2010
Microsoft Excel 2016

*Windows OS and Microsoft Excel are products of Microsoft Corporation.

The optional USB cable is also required.

- USB cable for RA-120 series
12AAH490

This program can be downloaded for FREE from the Mitutoyo website.
<https://www.mitutoyo.co.jp/eng/>


Specifications

Main unit


Model	RA-120		RA-120P	
	Dedicated electronic analysis type		Data analysis by PC	
Turntable	Rotational accuracy	Radial Axial	(0.04+6 H/10000) μm	H: Probing height (mm) JISB7451-1997 (0.04+6X/10000) μm X: Distance from the center of rotation (mm)
	Rotational speed			6 rpm
	Table diameter			150 mm
	Centering range adjustment			± 3 mm
	Leveling range adjustment			$\pm 1^\circ$
	Centering/leveling device (micrometer head)	Analog head	Digital head (mm)	Digital head (inch/mm)
	Maximum probing diameter			280 mm (380 mm in a reverse and vertical detector position)
	Maximum workpiece diameter			440 mm
	Maximum turntable loading			25 kg
Vertical column (Z axis)	Vertical travel			280 mm from the turntable top
	Maximum probing height			280 mm from the turntable top (480 mm in the reverse and vertical detector configuration)
	Maximum probing depth			100 mm (minimum ID: 30 mm)
Horizontal arm (X axis)	Horizontal travel			165 mm (Including a protrusion of 25 mm from the turntable rotation center)
Detector	Measuring direction			Two directional (IN/OUT switchable)
	Measuring range			$\pm 1000 \mu\text{m}$
	Measuring force			70 to 100 mN ($\pm 30\%$)
	Standard stylus (12AAL021)			Carbide ball, $\varnothing 1.6 \text{ mm}$ (.06")
Electronic unit	Measuring range			8 steps: $\pm(1000, 500, 200, 100, 50, 20, 10, 5) \mu\text{m}$
	Magnification	X5 to X200,000		X1 to X500,000
	Filter type	Phase corrected: Gaussian, 2CRPC75, 2CRPC50	Not phase corrected: 2CR75, 2CR50	Filter OFF
	Cutoff value	15 upr, 50 upr, 150 upr, 500 upr 15-150 upr, 15-500 upr, 50-500 upr	15 upr, 50 upr, 150 upr, 500 upr, Manual 15-150 upr, 15-500 upr, 50-500 upr, Manual	
	Number of measuring sections	Maximum 5		Maximum 100
	Evaluation type	Roundness, coaxality, concentricity, flatness, circular run-out (radial/axial), squareness (relative to axis/plane), thickness deviation, parallelism		
	Reference circle for evaluation	LSC, MZC, MIC, MCC		
	Adjusting centering/leveling	DAT function (circular/multi-point switchable)		
	Functions	Notched measurement, re-calculation, limacon error correction, continuous ID and OD measurement	Notched measurement, re-calculation, limacon error correction, remarkable point analysis (gear), harmonic analysis, continuous ID and OD measurement	
	Printer	Built-in thermal line printer, optional external printer	Windows compatible ink-jet printer	
	Display languages	Japanese, English, German, French, Italian, Spanish, Portuguese, Korean, Traditional Chinese, Simplified Chinese, Czech, Polish, Hungarian, Turkish, Swedish, Russian, Dutch, Thai	Japanese, English, German, French, Italian, Spanish, Portuguese, Korean, Traditional Chinese, Simplified Chinese, Czech, Polish, Hungarian, Turkish, Swedish, Russian, Dutch, Thai	
Others	USB	Calculation result, measurement data		
	Data output RS-232C	Calculation result, measurement data		
	SPC	Calculation result		
	Power supply	AC 100 – 240 V		
Others	Power consumption	32 – 36 W	21 – 24 W (excluding PC system)	
	Air pressure		0.39 MPa	
	Air consumption		30 L/min (minimum)	
	Mass	Main unit: 32 kg	Air filter: 2 kg	

Dimensions


External dimensions




Turntable top view



Installation floor plan





Whatever your challenges are, Mitutoyo supports you from start to finish.

Mitutoyo is not only a manufacturer of top quality measuring products but one that also offers qualified support for the lifetime of the equipment, backed up by comprehensive services that ensure your staff can make the very best use of the investment.

Apart from the basics of calibration and repair, Mitutoyo offers product and metrology training, as well as IT support for the sophisticated software used in modern measuring technology. We can also design, build, test and deliver measuring solutions and even, if deemed cost-effective, take your critical measurement challenges in-house on a sub-contract basis.



**Find additional product literature
and our product catalogue**

<https://www.mitutoyo.co.jp/global.html>

Our products are classified as regulated items under Japanese Foreign Exchange and Foreign Trade Law. Please consult us in advance if you wish to export our products to any other country. If the purchased product is exported, even though it is not a regulated item (Catch-All controls item), the customer service available for that product may be affected. If you have any questions, please consult your local Mitutoyo sales office.

Note: Product illustrations are without obligation. Product descriptions, in particular any and all technical specifications, are only binding when explicitly agreed upon.
MITUTOYO and MiCAT are either registered trademarks or trademarks of Mitutoyo Corp. in Japan and/or other countries/regions. Other product, company and brand names mentioned herein are for identification purposes only and may be the trademarks of their respective holders.

Mitutoyo

Mitutoyo Corporation

20-1, Sakado 1-Chome,
Takatsu-ku, Kawasaki-shi,
Kanagawa 213-8533, Japan

T +81 (0) 44 813-8230
F +81 (0) 44 813-8231
<https://www.mitutoyo.co.jp>